

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) In a first device for transferring a digital signal, a method of exchanging data between the first device and a second device comprising the steps of:
 - a) establishing a connection, for transferring said digital signal comprising large packets, between said first device and said second device;
 - b) negotiating the ~~maximum~~ size of packets for transfer between said first device and said second device;
 - c) in response to said negotiation, a communication layer of code coupled to said first device receiving a at least one packet from said second device;
 - d) in response to said received packet, said communication layer of code sending a response to said second device ~~for each of said packets received in step c)~~; and
 - e) repeating steps c) and d) until all packets from said second device are received; and
 - f) said communication layer transferring all of said packets as a single group to a processing layer of code coupled to said first device, wherein said processing code and said communication code are independent from each other, and wherein said processing layer of code performs authentication and also determines compliance with a copy protection scheme.

2. (Previously Presented) The method of Claim 1 wherein step c) comprises the steps of:

- c1) receiving a packet;
- c2) determining whether said packet is a fragmented packet;
- c3) if said packet is a fragmented packet, said communication layer of code storing said fragmented packet in a temporary buffer coupled to said first device; and
- c4) if said received packet was not the last packet to be received from said second device, repeating steps c1) – c3).

3. (Previously Presented) The method of Claim 1, wherein step c) comprises the step of: c1) receiving an un-fragmented packet of data.

4. (Cancelled)

5. (Previously Presented) The method of Claim 1 wherein said packet in step c) comprises an audio/video control (AV/C) command.

6. (Previously Presented) The method of Claim 1 wherein step d) comprising the step of: d1) said communication layer of code sending an audio/video control (AV/C) response to said second device for each of said packets received in step c).

7. (Original) The method of Claim 1 wherein said connection in step a) is made via an IEEE 1394 serial cable.

8. (Original) The method of Claim 1 wherein said packet comprises information regarding said second device's compliance with a copy protection scheme.

9. (Currently Amended) In a first device for transferring a digital signal, a method of exchanging data between the first device and a second device comprising the steps of:

a) establishing a connection, for transferring said digital signal comprising large packets, between said first device and said second device;

b) a communication layer of code coupled to said first device negotiating the ~~maximum~~ size of packets transferred between said first device and said second device;

c) in response to said negotiation, said communication layer of code sending at least one a packet of authentication information to said second device;

d) in response to said received packet, said communication layer of code receiving a response from said second device ~~for each of said packets sent in step c);~~

e) repeating steps c) and d) until all packets are sent; and

f) said communication layer transferring a response to a processing layer of code coupled to said first device, wherein said communication layer of code and said processing layer of code are independent from each other, wherein said processing layer performs authentication and determines said second device's compliance with a copy protection scheme, and wherein fragmentation of said packets is transparent to said processing layer.

10. (Original) The method of Claim 9 wherein said first device is a sink device and said second device is a source device.

11. (Previously Presented) The method of Claim 9 wherein said packet in step c) comprises an audio/video control (AV/C) command.

12. (Previously Presented) The method of Claim 9 wherein said response in step d) comprises a response to an audio/video control (AV/C) command.

13. (Currently Amended) A host device for processing digital audio/video signals comprising:

a) a processor coupled to a bus;

b) a memory coupled to said bus;

c) a communication layer of code stored in said memory and, when run in said processor, operable to establish a connection for transferring said digital audio/video signals comprising large packets, and negotiate the maximum size of packets transferred between said host device and a peripheral device, and said communication layer of code further operable to receive packets comprising authentication information from said peripheral device connected to said bus via a communication link; and

(d) a processing layer of code stored in said memory and, when executed in said processor, operable to perform authentication and key exchange and further operable to determine said peripheral device's compliance with a copy protection scheme;

said communication layer of code further operable to send a response to said peripheral device for each packet received from said peripheral device; and

said communication layer of code further operable to send all received packets as a single group to said processing layer of code stored in said memory, wherein fragmentation of said packets comprising authentication information is transparent to said processing layer operable to perform authentication and key exchange.

14. (Original) The device for processing digital audio/video signals of Claim 13 wherein:

said host device further comprises a temporary buffer stored in said memory;

wherein said communication layer of code is further operable to determine whether said packets received in step c) are fragmented packets; and

wherein said communication layer of code is further operable to store said fragmented packets in said temporary buffer.

15. (Original) The device for processing digital audio/video signals of Claim 13 wherein one of said packet in c) comprises an audio/video control (AV/C) command.

16. (Original) The device for processing digital audio/video signals of Claim 13 wherein said response in d) comprises a response to an audio/video control AV/C command.

17. (Original) The device for processing digital audio/video signals of Claim 13 wherein said host device is a sink device.
18. (Original) The device for processing digital audio/video signals of Claim 13 wherein said host device is a source device.
19. (Original) The device for processing digital audio/video signals of Claim 13 wherein said host device seeks full authentication.
20. (Original) The device for processing digital audio/video signals of Claim 13 wherein said host device seeks restricted authentication.
21. (Original) The device for processing digital audio/video signals of Claim 13 wherein said packets comprise information which defines that the peripheral device sending the packet is compliant with a copy protection scheme.
22. (New) The method of Claim 1, wherein said negotiating maximizes the size of packets for transfer between said first and said second device.
23. (New) The method of Claim 9, wherein said negotiating maximizes the size of packets for transfer between said first and said second device.

24. (New) The device for processing digital audio/video signals of Claim 13, wherein said negotiating maximizes the size of packets transferred between said host device and a peripheral device.